

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>G06F 1/00, 12/14</b>		<b>A1</b>	(11) International Publication Number: <b>WO 00/48063</b>
			(43) International Publication Date: 17 August 2000 (17.08.00)
(21) International Application Number: <b>PCT/GB00/00528</b>		(74) Agent: LAWRENCE, Richard, Anthony; Hewlett-Packard Limited, Intellectual Property Section, Filton Road, Stoke Gifford, Bristol BS34 8QZ (GB).	
(22) International Filing Date: 15 February 2000 (15.02.00)			
(30) Priority Data: 99301100.6 15 February 1999 (15.02.99) EP 9905056.9 5 March 1999 (05.03.99) GB		(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(71) Applicant (for all designated States except US): HEWLETT-PACKARD COMPANY [US/US]; 3000 Hanover Street, Palo Alto, CA 94304 (US).		Published With international search report.	
(72) Inventors; and (75) Inventors/Applicants (for US only): PROUDLER, Graeme, John [GB/GB]; 5 Touchstone Avenue, Stoke Gifford, Bristol BS34 8XQ (GB). GUPTA, Dipankar [IN/US]; 983 Sladky Ave., Mountain View, CA 94040 (US). CHEN, Liqun [CN/GB]; 1 Harvest Close, Bradley Stoke, Bristol BS32 9DQ (GB). PEARSON, Siani, Lynne [GB/GB]; 35 Sandyleaze, Westbury on Trym, Bristol BS9 3PZ (GB). BALACHEFF, Boris [FR/GB]; 215 High Kingsdown, St Michael's Hill, Bristol BS2 8DG (GB). VAN WILDER, Bruno, Edgard [BE/BE]; 1/3 Bauwensplaats, B-9300 Aalst (BE). CHAN, David [GB/US]; 16112 Mays Avenue, Monte Sereno, CA 95030 (US).			

(54) Title: TRUSTED COMPUTING PLATFORM

(57) Abstract

In a computing platform, a trusted hardware device (24) is added to the motherboard (20). The trusted hardware device (24) is configured to acquire an integrity metric, for example a hash of the BIOS memory (29), of the computing platform. The trusted hardware device (24) is tamper-resistant, difficult to forge and inaccessible to other functions of the platform (hardware or software) has not been subverted in some way, and is safe to interact with in local or remote applications. In more details, the main processing unit (21) of the computing platform is directed to address the trusted hardware device (24), in advance of the BIOS memory, after release from "reset". The trusted hardware device (24) is configured to receive memory read signals from the main processing unit (21) and, in response, return instructions, in the native language of main processing unit (21), that instruct the main processing unit to establish the hash and return the value to be stored by the trusted hardware device (24). Since the hash is calculated in advance of any other system operations, this is a relatively strong method of verifying the integrity of the system. Once the hash has been returned, the final instruction calls the BIOS program and the system boot procedure continues as normal. Whenever a user wishes to interact with the computing platform, he first requests the integrity metric, which he compares with an authentic integrity metric that was measured by a trusted party. If the metrics are the same, the platform is verified and interactions can continue. Otherwise, interaction halts on the basis that the operation of the platform may have been subverted.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## Trusted Computing Platform

### Technical Field

The present invention generally relates to trusted devices, trusted computing  
5 platforms, trusted transactions and methods of operating the same.

### Background Art

For commercial applications, a client computing platform typically operates in an environment where its behaviour is vulnerable to modification by local or remote entities.  
10 This potential insecurity of the platform is a limitation on its use by local parties who might otherwise be willing to use the platform, or remote parties who might otherwise communicate with the platform; for example, for the purposes of E-commerce. For the present purposes, both local parties and remote parties will be referred to as "users" unless otherwise stated.

Existing security applications, for example virus detection software, execute on  
15 computing platforms under the assumption that the platform will operate as intended and that the platform will not subvert processes and applications. This is a valid assumption provided that the intended software state has not become unstable or has not been damaged by other software such as viruses. Users, therefore, typically restrict the use of such platforms to non-critical applications, and weigh the convenience of using the platforms  
20 against the risk to sensitive or business critical data.

Increasing the level of trust in platforms therefore enables greater user confidence in existing security applications (such as the 'Secure Sockets Layer' or 'IPSec') or remote management applications. This enables greater reliance on those applications and hence reduced 'cost of ownership'. Greater trust also enables new electronic methods of business,  
25 since there is greater confidence in the correct operation of both local and remote computing platforms.

In this document, the word 'trust' is used in the sense that something can be 'trusted' if it always behaves in the expected manner for the intended purpose.

### 30 Disclosure of the Invention

The present inventors have appreciated that it is desirable to use a physical device in a computing platform to verify and possibly enforce trust in that platform. Typically, the device provides trusted measurement and reporting of attributes of the associated platform, which indicate the integrity of the platform. Also, most preferably, the device is tamper-  
35 resistant.

In accordance with a first aspect, the present invention provides computing apparatus comprising, mounted on an assembly, main processing means and main memory means, each being connected for communication with one or more other components on the assembly, together with a trusted device mounted on the assembly and being connected for  
5 communications with one or more other components on the assembly, the trusted device being arranged to acquire a true value of an integrity metric of the computing apparatus.

As used herein for reasons of simplicity of description, the term "device" also encompasses plural devices having equivalent function, or equivalent functionality integrated into one or more existing platform devices or assemblies. Additionally, the term 'true' as  
10 used herein implies that the value is that which correctly reflects the state of the computing apparatus. This may be ensured if the measurement method is substantially un-modifiable other than by the trusted device.

In accordance with a second aspect, the present invention provides a method of operating a system comprising trusted computing apparatus and a user, the trusted  
15 computing apparatus incorporating a trusted device being arranged to acquire the true value of an integrity metric of the computing apparatus, the method comprising the steps of:

the trusted device acquiring the true value of the integrity metric of the trusted computing apparatus;

the user generating a challenge for the trusted computing apparatus to prove its  
20 integrity and submitting the challenge to the trusted computing apparatus;

the trusted computing apparatus receiving the challenge, and the trusted device generating a response including the integrity metric and returning the response to the user;  
and

the user receiving the response, extracting the integrity metric from the response and  
25 comparing the integrity metric with an authenticated metric for the trusted computing apparatus that had been generated by a trusted party.

In accordance with a third aspect, the present invention provides a method of establishing a communications channel in a system between trusted computing apparatus and remote computing apparatus, the method including the step of the remote computing  
30 apparatus verifying the integrity of the trusted computing apparatus using the above method, and maintaining the communications channel for further transactions in the event the integrity of the trusted computing apparatus is successfully verified by the remote computing apparatus.

In accordance with a fourth embodiment, the present invention provides a method of  
35 verifying that trusted computing apparatus is trustworthy for use by a user for processing a

particular application, the method including the step of the user verifying the integrity of the trusted computing apparatus using the above method, and the user using the trusted computing apparatus to process the particular application in the event the integrity of the trusted computing apparatus is successfully verified by the remote computing apparatus.

5 Other aspects and embodiments of the present invention will become apparent from the following description and claims.

#### Brief Description of the Drawings

A preferred embodiment of the present invention will now be described by way of  
10 example only with reference to the accompanying drawings in which:

Figure 1 is a diagram that illustrates a system capable of implementing embodiments of the present invention;

Figure 2 is a diagram which illustrates a motherboard including a trusted device arranged to communicate with a smart card via a smart card reader and with a group of  
15 modules;

Figure 3 is a diagram that illustrates the trusted device in more detail;

Figure 4 is a flow diagram which illustrates the steps involved in acquiring an integrity metric of the computing apparatus;

Figure 5 is a flow diagram which illustrates the steps involved in establishing  
20 communications between a trusted computing platform and a remote platform including the trusted platform verifying its integrity; and

Figure 6 is a flow diagram which illustrates the steps involved in verification of a trusted computing platform by a potential user of that platform by means of a smart card.

#### 25 Best Mode For Carrying Out the Invention, & Industrial Applicability

The present exemplary embodiment generally provides the incorporation into a computing platform of a physical trusted device whose function is to bind the identity of the platform to reliably measured data that provides an integrity metric of the platform. The identity and the integrity metric are compared with expected values provided by a trusted  
30 party (TP) that is prepared to vouch for the trustworthiness of the platform. If there is a match, the implication is that at least part of the platform is operating correctly, depending on the scope of the integrity metric.

A user verifies the correct operation of the platform before exchanging other data with the platform. A user does this by requesting the trusted device to provide its identity  
35 and an integrity metric. (Optionally the trusted device will refuse to provide evidence of

identity if it itself was unable to verify correct operation of the platform.) The user receives the proof of identity and the identity metric, and compares them against values which it believes to be true. Those proper values are provided by the TP or another entity that is trusted by the user. If data reported by the trusted device is the same as that provided by  
5 the TP, the user trusts the platform. This is because the user trusts the entity. The entity trusts the platform because it has previously validated the identity and determined the proper integrity metric of the platform.

Once a user has established trusted operation of the platform, he exchanges other data with the platform. For a local user, the exchange might be by interacting with some  
10 software application running on the platform. For a remote user, the exchange might involve a secure transaction. In either case, the data exchanged is 'signed' by the trusted device. The user can then have greater confidence that data is being exchanged with a platform whose behaviour can be trusted.

The trusted device uses cryptographic processes but does not necessarily provide an  
15 external interface to those cryptographic processes. Also, a most desirable implementation would be to make the trusted device tamperproof, to protect secrets by making them inaccessible to other platform functions and provide an environment that is substantially immune to unauthorised modification. Since tamper-proofing is impossible, the best approximation is a trusted device that is tamper-resistant, or tamper-detecting. The trusted  
20 device, therefore, preferably consists of one physical component that is tamper-resistant.

Techniques relevant to tamper-resistance are well known to those skilled in the art of security. These techniques include methods for resisting tampering (such as appropriate encapsulation of the trusted device), methods for detecting tampering (such as detection of out of specification voltages, X-rays, or loss of physical integrity in the trusted device casing),  
25 and methods for eliminating data when tampering is detected. Further discussion of appropriate techniques can be found at <http://www.cl.cam.ac.uk/~mgk25/tamper.html>. It will be appreciated that, although tamper-proofing is a most desirable feature of the present invention, it does not enter into the normal operation of the invention and, as such, is beyond the scope of the present invention and will not be described in any detail herein.

30 The trusted device is preferably a physical one because it must be difficult to forge. It is most preferably tamper-resistant because it must be hard to counterfeit. It typically has an engine capable of using cryptographic processes because it is required to prove identity, both locally and at a distance, and it contains at least one method of measuring some integrity metric of the platform with which it is associated.

A trusted platform 10 is illustrated in the diagram in Figure 1. The platform 10 includes the standard features of a keyboard 14, mouse 16 and visual display unit (VDU) 18, which provide the physical 'user interface' of the platform. This embodiment of a trusted platform also contains a smart card reader 12 - a smart card reader is not an essential  
5 element of all trusted platforms, but is employed in various preferred embodiments described below. Along side the smart card reader 12, there is illustrated a smart card 19 to allow trusted user interaction with the trusted platform as shall be described further below. In the platform 10, there are a plurality of modules 15: these are other functional elements of the trusted platform of essentially any kind appropriate to that platform (the functional  
10 significance of such elements is not relevant to the present invention and will not be discussed further herein).

As illustrated in Figure 2, the motherboard 20 of the trusted computing platform 10 includes (among other standard components) a main processor 21, main memory 22, a trusted device 24, a data bus 26 and respective control lines 27 and lines 28, BIOS memory  
15 29 containing the BIOS program for the platform 10 and an Input/Output (IO) device 23, which controls interaction between the components of the motherboard and the smart card reader 12, the keyboard 14, the mouse 16 and the VDU 18. The main memory 22 is typically random access memory (RAM). In operation, the platform 10 loads the operating system, for example Windows NT™, into RAM from hard disk (not shown). Additionally, in  
20 operation, the platform 10 loads the processes or applications that may be executed by the platform 10 into RAM from hard disk (not shown).

Typically, in a personal computer the BIOS program is located in a special reserved memory area, the upper 64K of the first megabyte of the system memory (addresses F000h to FFFFh), and the main processor is arranged to look at this memory location first,  
25 in accordance with an industry wide standard.

The significant difference between the platform and a conventional platform is that, after reset, the main processor is initially controlled by the trusted device, which then hands control over to the platform-specific BIOS program, which in turn initialises all input/output devices as normal. After the BIOS program has executed, control is handed over as normal  
30 by the BIOS program to an operating system program, such as Windows NT (TM), which is typically loaded into main memory 22 from a hard disk drive (not shown).

Clearly, this change from the normal procedure requires a modification to the implementation of the industry standard, whereby the main processor 21 is directed to address the trusted device 24 to receive its first instructions. This change may be made  
35 simply by hard-coding a different address into the main processor 21. Alternatively, the

trusted device 24 may be assigned the standard BIOS program address, in which case there is no need to modify the main processor configuration.

It is highly desirable for the BIOS boot block to be contained within the trusted device 24. This prevents subversion of the obtaining of the integrity metric (which could otherwise occur if rogue software processes are present) and prevents rogue software processes creating a situation in which the BIOS (even if correct) fails to build the proper environment for the operating system.

Although, in the preferred embodiment to be described, the trusted device 24 is a single, discrete component, it is envisaged that the functions of the trusted device 24 may alternatively be split into multiple devices on the motherboard, or even integrated into one or more of the existing standard devices of the platform. For example, it is feasible to integrate one or more of the functions of the trusted device into the main processor itself, provided that the functions and their communications cannot be subverted. This, however, would probably require separate leads on the processor for sole use by the trusted functions. Additionally or alternatively, although in the present embodiment the trusted device is a hardware device that is adapted for integration into the motherboard 20, it is anticipated that a trusted device may be implemented as a 'removable' device, such as a dongle, which could be attached to a platform when required. Whether the trusted device is integrated or removable is a matter of design choice. However, where the trusted device is separable, a mechanism for providing a logical binding between the trusted device and the platform should be present.

The trusted device 24 comprises a number of blocks, as illustrated in Figure 3. After system reset, the trusted device 24 performs a secure boot process to ensure that the operating system of the platform 10 (including the system clock and the display on the monitor) is running properly and in a secure manner. During the secure boot process, the trusted device 24 acquires an integrity metric of the computing platform 10. The trusted device 24 can also perform secure data transfer and, for example, authentication between it and a smart card via encryption/decryption and signature/verification. The trusted device 24 can also securely enforce various security control policies, such as locking of the user interface.

Specifically, the trusted device comprises: a controller 30 programmed to control the overall operation of the trusted device 24, and interact with the other functions on the trusted device 24 and with the other devices on the motherboard 20; a measurement function 31 for acquiring the integrity metric from the platform 10; a cryptographic function 32 for signing, encrypting or decrypting specified data; an authentication function 33 for authenticating a



smart card; and interface circuitry 34 having appropriate ports (36, 37 & 38) for connecting the trusted device 24 respectively to the data bus 26, control lines 27 and address lines 28 of the motherboard 20. Each of the blocks in the trusted device 24 has access (typically via the controller 30) to appropriate volatile memory areas 4 and/or non-volatile memory areas 3 of the trusted device 24. Additionally, the trusted device 24 is designed, in a known manner, to be tamper resistant.

For reasons of performance, the trusted device 24 may be implemented as an application specific integrated circuit (ASIC). However, for flexibility, the trusted device 24 is preferably an appropriately programmed micro-controller. Both ASICs and micro-controllers are well known in the art of microelectronics and will not be considered herein in any further detail.

One item of data stored in the non-volatile memory 3 of the trusted device 24 is a certificate 350. The certificate 350 contains at least a public key 351 of the trusted device 24 and an authenticated value 352 of the platform integrity metric measured by a trusted party (TP). The certificate 350 is signed by the TP using the TP's private key prior to it being stored in the trusted device 24. In later communications sessions, a user of the platform 10 can verify the integrity of the platform 10 by comparing the acquired integrity metric with the authentic integrity metric 352. If there is a match, the user can be confident that the platform 10 has not been subverted. Knowledge of the TP's generally-available public key enables simple verification of the certificate 350. The non-volatile memory 35 also contains an identity (ID) label 353. The ID label 353 is a conventional ID label, for example a serial number, that is unique within some context. The ID label 353 is generally used for indexing and labelling of data relevant to the trusted device 24, but is insufficient in itself to prove the identity of the platform 10 under trusted conditions.

The trusted device 24 is equipped with at least one method of reliably measuring or acquiring the integrity metric of the computing platform 10 with which it is associated. In the present embodiment, the integrity metric is acquired by the measurement function 31 by generating a digest of the BIOS instructions in the BIOS memory. Such an acquired integrity metric, if verified as described above, gives a potential user of the platform 10 a high level of confidence that the platform 10 has not been subverted at a hardware, or BIOS program, level. Other known processes, for example virus checkers, will typically be in place to check that the operating system and application program code has not been subverted.

The measurement function 31 has access to: non-volatile memory 3 for storing a hash program 354 and a private key 355 of the trusted device 24, and volatile memory 4 for storing acquired integrity metric in the form of a digest 361. In appropriate embodiments, the

volatile memory 4 may also be used to store the public keys and associated ID labels 360a-360n of one or more authentic smart cards 19s that can be used to gain access to the platform 10.

In one preferred implementation, as well as the digest, the integrity metric includes a Boolean value, which is stored in volatile memory 4 by the measurement function 31, for reasons that will become apparent.

A preferred process for acquiring an integrity metric will now be described with reference to Figure 4.

In step 500, at switch-on, the measurement function 31 monitors the activity of the main processor 21 on the data, control and address lines (26, 27 & 28) to determine whether the trusted device 24 is the first memory accessed. Under conventional operation, a main processor would first be directed to the BIOS memory first in order to execute the BIOS program. However, in accordance with the present embodiment, the main processor 21 is directed to the trusted device 24, which acts as a memory. In step 505, if the trusted device 24 is the first memory accessed, in step 510, the measurement function 31 writes to volatile memory 3 a Boolean value which indicates that the trusted device 24 was the first memory accessed. Otherwise, in step 515, the measurement function writes a Boolean value which indicates that the trusted device 24 was not the first memory accessed.

In the event the trusted device 24 is not the first accessed, there is of course a chance that the trusted device 24 will not be accessed at all. This would be the case, for example, if the main processor 21 were manipulated to run the BIOS program first. Under these circumstances, the platform would operate, but would be unable to verify its integrity on demand, since the integrity metric would not be available. Further, if the trusted device 24 were accessed after the BIOS program had been accessed, the Boolean value would clearly indicate lack of integrity of the platform.

In step 520, when (or if) accessed as a memory by the main processor 21, the main processor 21 reads the stored native hash instructions 354 from the measurement function 31 in step 525. The hash instructions 354 are passed for processing by the main processor 21 over the data bus 26. In step 530, main processor 21 executes the hash instructions 354 and uses them, in step 535, to compute a digest of the BIOS memory 29, by reading the contents of the BIOS memory 29 and processing those contents according to the hash program. In step 540, the main processor 21 writes the computed digest 361 to the appropriate non-volatile memory location 4 in the trusted device 24. The measurement function 31, in step 545, then calls the BIOS program in the BIOS memory 29, and execution continues in a conventional manner.

Clearly, there are a number of different ways in which the integrity metric may be calculated, depending upon the scope of the trust required. The measurement of the BIOS program's integrity provides a fundamental check on the integrity of a platform's underlying processing environment. The integrity metric should be of such a form that it will enable  
5 reasoning about the validity of the boot process - the value of the integrity metric can be used to verify whether the platform booted using the correct BIOS. Optionally, individual functional blocks within the BIOS could have their own digest values, with an ensemble BIOS digest being a digest of these individual digests. This enables a policy to state which parts of BIOS operation are critical for an intended purpose, and which are irrelevant (in  
10 which case the individual digests must be stored in such a manner that validity of operation under the policy can be established).

Other integrity checks could involve establishing that various other devices, components or apparatus attached to the platform are present and in correct working order. In one example, the BIOS programs associated with a SCSI controller could be verified to  
15 ensure communications with peripheral equipment could be trusted. In another example, the integrity of other devices, for example memory devices or co-processors, on the platform could be verified by enacting fixed challenge/response interactions to ensure consistent results. Where the trusted device 24 is a separable component, some such form of interaction is desirable to provide an appropriate logical binding between the trusted device  
20 14 and the platform. Also, although in the present embodiment the trusted device 24 utilises the data bus as its main means of communication with other parts of the platform, it would be feasible, although not so convenient, to provide alternative communications paths, such as hard-wired paths or optical paths. Further, although in the present embodiment the trusted device 24 instructs the main processor 21 to calculate the integrity metric in other  
25 embodiments, the trusted device itself is arranged to measure one or more integrity metrics.

Preferably, the BIOS boot process includes mechanisms to verify the integrity of the boot process itself. Such mechanisms are already known from, for example, Intel's draft "Wired for Management baseline specification v 2.0 - BOOT Integrity Service", and involve calculating digests of software or firmware before loading that software or firmware. Such a  
30 computed digest is compared with a value stored in a certificate provided by a trusted entity, whose public key is known to the BIOS. The software/firmware is then loaded only if the computed value matches the expected value from the certificate, and the certificate has been proven valid by use of the trusted entity's public key. Otherwise, an appropriate exception handling routine is invoked.

Optionally, after receiving the computed BIOS digest, the trusted device 24 may inspect the proper value of the BIOS digest in the certificate and not pass control to the BIOS if the computed digest does not match the proper value. Additionally, or alternatively, the trusted device 24 may inspect the Boolean value and not pass control back to the BIOS if the trusted device 24 was not the first memory accessed. In either of these cases, an appropriate exception handling routine may be invoked.

Figure 5 illustrates the flow of actions by a TP, the trusted device 24 incorporated into a platform, and a user (of a remote platform) who wants to verify the integrity of the trusted platform. It will be appreciated that substantially the same steps as are depicted in Figure 5 are involved when the user is a local user. In either case, the user would typically rely on some form of software application to enact the verification. It would be possible to run the software application on the remote platform or the trusted platform. However, there is a chance that, even on the remote platform, the software application could be subverted in some way. Therefore, it is anticipated that, for a high level of integrity, the software application would reside on a smart card of the user, who would insert the smart card into an appropriate reader for the purposes of verification. Figure 5 illustrates the flow of actions for the general case - a more specific flow of actions for verification by a user smart card will be described with reference to Figure 6 further below.

At the first instance, a TP, which vouches for trusted platforms, will inspect the type of the platform to decide whether to vouch for it or not. This will be a matter of policy. If all is well, in step 600, the TP measures the value of integrity metric of the platform. Then, the TP generates a certificate, in step 605, for the platform. The certificate is generated by the TP by appending the trusted device's public key, and optionally its ID label, to the measured integrity metric, and signing the string with the TP's private key.

The trusted device 24 can subsequently prove its identity by using its private key to process some input data received from the user and produce output data, such that the input/output pair is statistically impossible to produce without knowledge of the private key. Hence, knowledge of the private key forms the basis of identity in this case. Clearly, it would be feasible to use symmetric encryption to form the basis of identity. However, the disadvantage of using symmetric encryption is that the user would need to share his secret with the trusted device. Further, as a result of the need to share the secret with the user, while symmetric encryption would in principle be sufficient to prove identity to the user, it would be insufficient to prove identity to a third party, who could not be entirely sure the verification originated from the trusted device or the user.

In step 610, the trusted device 24 is initialised by writing the certificate 350 into the appropriate non-volatile memory locations 3 of the trusted device 24. This is done, preferably, by secure communication with the trusted device 24 after it is installed in the motherboard 20. The method of writing the certificate to the trusted device 24 is analogous  
5 to the method used to initialise smart cards by writing private keys thereto. The secure communications is supported by a 'master key', known only to the TP, that is written to the trusted device (or smart card) during manufacture, and used to enable the writing of data to the trusted device 24; writing of data to the trusted device 24 without knowledge of the master key is not possible.

10 At some later point during operation of the platform, for example when it is switched on or reset, in step 615, the trusted device 24 acquires and stores the integrity metric 361 of the platform.

When a user wishes to communicate with the platform, in step 620, he creates a nonce, such as a random number, and, in step 625, challenges the trusted device 24 (the  
15 operating system of the platform, or an appropriate software application, is arranged to recognise the challenge and pass it to the trusted device 24, typically via a BIOS-type call, in an appropriate fashion). The nonce is used to protect the user from deception caused by replay of old but genuine signatures (called a 'replay attack') by untrustworthy platforms. The process of providing a nonce and verifying the response is an example of the well-  
20 known 'challenge/response' process.

In step 630, the trusted device 24 receives the challenge and creates an appropriate response. This may be a digest of the measured integrity metric and the nonce, and optionally its ID label. Then, in step 635, the trusted device 24 signs the digest, using its private key, and returns the signed digest, accompanied by the certificate 350, to the user.

25 In step 640, the user receives the challenge response and verifies the certificate using the well known public key of the TP. The user then, in step 650, extracts the trusted device's 24 public key from the certificate and uses it to decrypt the signed digest from the challenge response. Then, in step 660, the user verifies the nonce inside the challenge response. Next, in step 670, the user compares the computed integrity metric, which it  
30 extracts from the challenge response, with the proper platform integrity metric, which it extracts from the certificate. If any of the foregoing verification steps fails, in steps 645, 655, 665 or 675, the whole process ends in step 680 with no further communications taking place.

Assuming all is well, in steps 685 and 690, the user and the trusted platform use other protocols to set up secure communications for other data, where the data from the  
35 platform is preferably signed by the trusted device 24.

Further refinements of this verification process are possible. It is desirable that the challenger becomes aware, through the challenge, both of the value of the platform integrity metric and also of the method by which it was obtained. Both these pieces of information are desirable to allow the challenger to make a proper decision about the integrity of the platform. The challenger also has many different options available - it may accept that the integrity metric is recognised as valid in the trusted device 24, or may alternatively only accept that the platform has the relevant level of integrity if the value of the integrity metric is equal to a value held by the challenger (or may hold there to be different levels of trust in these two cases).

10 The techniques of signing, using certificates, and challenge/response, and using them to prove identity, are well known to those skilled in the art of security and therefore need not be described in any more detail herein.

As indicated above, Figure 6 shows the flow of actions in an example of verification of platform integrity by a user interacting with the trusted platform with a smart card 19. As will be described, the process conveniently implements a challenge/response routine. There exist many available challenge/response mechanisms. The implementation of an authentication protocol used in the present embodiment is mutual (or 3-step) authentication, as described in ISO/IEC 9798-3, "Information technology - Security techniques - Entity authentication mechanisms; Part 3; Entity authentication using a public key algorithm", 20 International Organization for Standardization, November 1993. Of course, there is no reason why other authentication procedures cannot be used, for example 2-step or 4-step, as also described in this reference.

Initially, the user inserts their smart card 19 into the smart card reader 12 of the platform in step 700.

25 Beforehand, a platform configured for use by users of in this way will typically be operating under the control of its standard operating system and executing the authentication process, which waits for a user to insert their smart card 19. Apart from the smart card reader 12 being active in this way, such a platform is typically rendered inaccessible to users by 'locking' the user interface (i.e. the screen, keyboard and mouse).

30 This will however not be the case in all embodiments of the invention.

When the smart card 19 is inserted into the smart card reader 12, the trusted device 24 is triggered to attempt mutual authentication in step by generating and transmitting a nonce A to the smart card 19 in step 705. A nonce, such as a random number, is used to protect the originator from deception caused by replay of old but genuine responses (called 35 a 'replay attack') by untrustworthy third parties.

In response, in step 710, the smart card 19 generates and returns a response comprising the concatenation of: the plain text of the nonce A, a new nonce B generated by the smart card 19, an ID of the trusted device 24 and some redundancy; the signature of the plain text, generated by signing the plain text with the private key of the smart card 19; and a  
5 certificate containing the ID and the public key of the smart card 19.

The trusted device 24 authenticates the response by using the public key in the certificate to verify the signature of the plain text in step 715. If the response is not authentic, the process ends in step 720. If the response is authentic, in step 725 the trusted device 24 generates and sends a further response including the concatenation of: the plain  
10 text of the nonce A, the nonce B, an ID of the smart card 19 and the acquired integrity metric; the signature of the plain text, generated by signing the plain text using the private key of the trusted device 24; and the certificate comprising the public key of the trusted device 24 and the authentic integrity metric, both signed by the private key of the TP.

The smart card 19 authenticates this response by using the public key of the TP and  
15 comparing the acquired integrity metric with the authentic integrity metric, where a match indicates successful verification, in step 730. If the further response is not authentic, the process ends in step 735.

If the procedure is successful, both the trusted device 24 has authenticated the logon card 19 and the smart card 19 has verified the integrity of the trusted platform and, in step  
20 740, the authentication process executes the secure process for the user.

In certain types of interaction, the authentication process can end at this point. However, if a session is to be continued between the user and the trusted platform, it is desirable to ensure that the user remains authenticated to the platform.

Where continued authentication is required, the authentication process sets an  
25 interval timer in step 745. Thereafter, using appropriate operating system interrupt routines, the authentication process services the interval timer periodically to detect when the timer meets or exceeds a pre-determined timeout period in step 750.

Clearly, the authentication process and the interval timer run in parallel with the secure process. When the timeout period is met or exceeded, the authentication process  
30 triggers the trusted device 24 to re-authenticate the smart card 19, by transmitting a challenge for the smart card 19 to identify itself in step 760. The smart card 19 returns a certificate including its ID and its public key in step 765. In step 770, if there is no response (for example, as a result of the smart card 19 having been removed) or the certificate is no longer valid for some reason (for example, the smart card has been replaced with a different

smart card), the session is terminated by the trusted device 24 in step 775. Otherwise, in step 770, the process from step 745 repeats by resetting the interval timer.

Additionally, or alternatively, in some embodiments it may be required that the user profile is encrypted and signed to protect privacy and integrity. If so, a secure data transfer  
5 protocol may be needed between the trusted device 24 and the smart card 19. There exist many available mechanisms for transferring secure credentials between two entities. A possible implementation, which may be used in the present embodiment, is secure key transport mechanisms from ISO/IEC DIS 11770-3, "Information technology – Security techniques – Key management - Part 3: Mechanisms using asymmetric techniques",  
10 International Organization for Standardization, March 1997.

Modifications of this verification process using other well-known challenge and response techniques can easily be achieved by the skilled person. Similarly, alternative verification processes can be used by parties interacting with the platform in a different manner (that is, other than as a user equipped with a smart card).



## CLAIMS

1. Computing apparatus comprising mounted on an assembly main processing means and  
5 main memory means, each being connected for communication with one or more other components on the assembly,  
characterised by further comprising a trusted device mounted on the assembly and  
being connected for communications with one or more other components on the assembly,  
the trusted device being arranged to acquire a true value of an integrity metric of the  
10 computing apparatus.
2. Computing apparatus according to claim 1, wherein the trusted device comprises device  
memory means and means for instructing the main processing means to determine the  
integrity metric and return the integrity metric for storage in the device memory means.  
15
3. Computing apparatus according to claim 2, wherein the means for instructing the main  
processing means comprises, stored in the device memory means, program code native to  
the main processing means, and the trusted device is arranged to transfer the instructions of  
the program code to the main processing means.  
20
4. Computing apparatus according to claim 3, wherein the platform is arranged to cause the  
instructions to be the first instructions executed after release from reset.
5. Computing apparatus according to claim 3 or claim 4, wherein the trusted device is  
25 arranged to transfer the instructions to the main processing means in response to memory  
read signals from the main processing means.
6. Computing apparatus according to any one of claims 1 to 5, wherein the trusted device  
comprises device memory means and is arranged to monitor the data bus means and store  
30 in the device memory means a flag in the event the first memory read signals generated by  
the main processing means after the computing apparatus is released from reset are  
addressed to the trusted device.

7. Computing apparatus according to any one of claims 1 to 6, wherein the trusted device has stored in device memory means at least one of:

- a unique identity of the trusted device;
- an authenticated integrity metric generated by a trusted party; and
- 5 a secret.

8. Computing apparatus according to claim 7, wherein the trusted device has stored in device memory means a secret comprising a private asymmetric encryption key.

10 9. Computing apparatus according to claim 8, wherein the trusted device also has stored in device memory means a respective public encryption key that has been signed by a trusted party.

10. Computing apparatus according to claim 8 or claim 9, wherein the trusted device has  
15 stored in device memory means an authenticated integrity metric generated by a trusted party and includes a encryption function, the trusted device being arranged to generate a response to a received challenge, the response comprising an acquired integrity metric and the authenticated integrity metric, both signed by the encryption function using the private asymmetric encryption key.

20

11. A trusted device configured for use in computing apparatus according to any one of the preceding claims.

12. A method of operating a system comprising trusted computing apparatus and a user,  
25 the trusted computing apparatus incorporating a trusted device being arranged to acquire the true value of an integrity metric of the computing apparatus, the method comprising the steps of:

- the trusted device acquiring the true value of the integrity metric of the trusted computing apparatus;

30 the user generating a challenge for the trusted computing apparatus to prove its integrity and submitting the challenge to the trusted computing apparatus;

- the trusted computing apparatus receiving the challenge, and the trusted device generating a response including the integrity metric and returning the response to the user; and

the user receiving the response, extracting the integrity metric from the response and comparing the integrity metric with an authenticated metric for the trusted computing apparatus that had been generated by a trusted party.

- 5 13. A method according to claim 12, wherein the challenge includes a nonce, the response includes the integrity metric and the nonce, both digitally signed by the trusted device using a information security algorithm, and the user verifies the integrity metric and the nonce using a respective information security algorithm.
- 10 14. A method according to claim 13, wherein the trusted device uses a private encryption key to sign the integrity metric and the nonce, and the user uses the respective public encryption key to verify the integrity metric and the nonce.
- 15 15. A method according to claim 14, wherein the response includes a certificate held by the trusted device, which certificate has been digitally signed by a trusted party using a private encryption key of the trusted party, the certificate including the public encryption key of the trusted device, and the user verifies the certificate using the public encryption key of the trusted party and uses the public encryption key from the certificate to verify the integrity metric and the nonce.
- 20
- 25 16. A method of establishing a communications channel in a system between trusted computing apparatus and remote computing apparatus, the method including the step of the remote computing apparatus verifying the integrity of the trusted computing apparatus using the method according to any one of claims 12 to 15, and maintaining the communications channel for further transactions in the event the integrity of the trusted computing apparatus is successfully verified by the remote computing apparatus.
- 30 17. A method of verifying that trusted computing apparatus is trustworthy for use by a user for processing a particular application, the method including the step of the user verifying the integrity of the trusted computing apparatus using the method according to any one of claims 12 to 15, and the user using the trusted computing apparatus to process the particular application in the event the integrity of the trusted computing apparatus is successfully verified by the remote computing apparatus.

18. Trusted computing apparatus adapted for use in accordance with the method of any one of claims 12 to 17.

19. Remote computing apparatus arranged for use in accordance with claim 16.


5

20. A trusted device arranged for use in accordance with any one of claims 12 to 17.


21. Computing apparatus configured to receive a trusted device as claimed in claim 11.

10

1/5





**FIGURE 1**




**FIGURE 2**

2/5



**3/5****FIGURE 4**

4/5

**FIGURE 5**



## 5/5




FIGURE 6

Internal Application No  
PCT/GB 00/00528

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 G06F1/00 G06F12/14

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

### C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	WO 98 15082 A (INTEL CORP) 9 April 1998 (1998-04-09) the whole document	1-4,7, 11,21
X A	EP 0 849 657 A (NCR INT INC) 24 June 1998 (1998-06-24) the whole document	5,8-10, 12-15
	—	1,2,7
	—	10
	—	
	—/—	

**Y** Further documents are listed in the continuation of box C.

**Y** Patent family members are listed in annex.

\* Special categories of cited documents :

**"A" document defining the general state of the art which is not considered to be of particular relevance**

**"E"** earlier document but published on or after the international filing date

2. document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

**"P"** document published prior to the international filing date but later than the priority date claimed

\* Later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

**X** document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

**"a" document member of the same patent family**

Date of the actual completion of the international search

**30 March 2000**

Date of mailing of the international search report

06/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

**Authorized officer**

**Powell, D**

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 00/00528

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 95 24696 A (INTEGRATED TECH AMERICA ;MOONEY DAVID M (US); WOOD DAVID E (US); K) 14 September 1995 (1995-09-14) abstract; figure 3 page 3, paragraph 3 page 9, paragraph 2 - paragraph 3 page 12, paragraph 3 -page 13, paragraph 1 page 19, last paragraph -page 20, paragraph 1 page 21, paragraph 1 -page 22, paragraph 2 page 27, paragraph 2 -page 28, paragraph 1 claims 4,16</p>	1,2,4, 6-8,10
A	<p>US 5 680 547 A (CHANG STEVE MING-JANG) 21 October 1997 (1997-10-21) the whole document</p>	16,19
A	<p>EP 0 510 244 A (ACER INC) 28 October 1992 (1992-10-28)</p>	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/00528

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9815082 A	09-04-1998	US 5844986 A AU 4146197 A CN 1231787 A EP 0932953 A	01-12-1998 24-04-1998 13-10-1999 04-08-1999
EP 0849657 A	24-06-1998	JP 10282884 A	23-10-1998
WO 9524696 A	14-09-1995	US 5610981 A AT 175505 T AU 703856 B AU 2092695 A BR 9506968 A CA 2183759 A CN 1146813 A DE 69507129 D DE 69507129 T EP 0748474 A NZ 282954 A	11-03-1997 15-01-1999 01-04-1999 25-09-1995 01-06-1999 14-09-1995 02-04-1997 18-02-1999 05-08-1999 18-12-1996 24-11-1997
US 5680547 A	21-10-1997	US 5444850 A AU 1042895 A JP 10511783 T WO 9613002 A	22-08-1995 15-05-1996 10-11-1998 02-05-1996
EP 0510244 A	28-10-1992	JP 6348486 A US 5511184 A	22-12-1994 23-04-1996